PRODUCT DATA SHEET

SikaBiresin® RA-841

LIQUID RELEASE AGENT FOR EPOXY AND POLYURETHANE SIKABIRESIN® SYSTEMS; WAX DISPERSION

APPLICATIONS				
	Release model r	agent for polyurethane, epoxy and silicon SikaBiresin® mold systems in making		
MAIN PROPERTIES				
		 Is well suited for complex geometries and has a temperature resistance up to 90 °C 		
	■ Watery	 Watery liquid, for application by brush or spray gun in two- or three-times coating Drying to a colorless film, is polishable 		
DESCRIPTION				
Basis	■ Wax dispersion, milky, low viscosity			
PACKAGING UNITS				
	■ SikaBiresin® RA 841		0,7 kg / 7 kg	
PHYSICAL PROPERTIES				
Density	g/ml	0.71 – 0,73		
Color		off white		
Flash point	°C	< 0		

PROCESSING DATA

- The material, processing and mold or mastermodel temperature must be at least 15 °C 25 °C.
- Make sure the mold is clean and dry and free of dust and grease before applying the release agent.
- The release agent must be shaken well before use.
- Apply release agent with a clean, lint-free cloth, brush or suitable spray gun.
- When using new molds for the first time, apply three coats of the release agent.
- Every subsequent usage of the mold a single coat of the release agent is workable.
- Each layer needs a drying time from approx. 10 minutes.
- It is possible to polish the surface of the release agent.
- The material must be sprayed with a distance of approx. 30 cm on the mold, only in one layer.
- Excess release agent can be removed with a cotton cloth.

STORAGE CONDITIONS

Shelf life	■ SikaBiresin® RA 841	12 months
Storage temperature	■ SikaBiresin® RA 841	18 – 25 °C

FURTHER INFORMATION

The information herein is offered for general guidance only. Advice on specific applications is available on request from the Technical Department of Sika Advanced Resins. Copies of the following publications are available on request: Safety Data Sheets

BASIS OF PRODUCT DATA

All technical data stated in this document are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

HEALTH AND SAFETY INFORMATION

For information and advice regarding transportation, handling, storage and disposal of chemical products, users shall refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTICE

The information, and, in particular, the recommendations relating to the application and enduse of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Contact

SIKA DEUTSCHLAND GMBH

Stuttgarter Straße 139 72574 Bad Urach - GERMANY Phone: +49 7125 940 492 Fax: +49 7125 940 401 E-Mail: tooling@de.sika.com Website: www.sikaadvancedresins.de

SIKA AUTOMOTIVE FRANCE S.A.S.

ZI des Béthunes - 15, Rue de l'Equerre 95310 Saint-Ouen-l'Aumône CS 40444

95005 Cergy Pontoise Cedex - FRANCE Phone: +33 1 34 40 34 60

Fax: +33 1 34 21 97 87

E-Mail: advanced.resins@fr.sika.com Website: www.sikaadvancedresins.fr

AXSON TECHNOLOGIES SPAIN, S.L.

C/Guardaagulles, 8 – P.I. Congost - 08520 Les Franqueses del Valles (Barcelona) - SPAIN Phone: +34 93 225 16 20

Fax: +34 93 225 03 05 E-Mail: spain@axson.com

Website: www.sikaadvancedresins.es

AXSON ITALIA S.R.L.

Via Morandi 15 21047 Saronno (Va) - ITALY Phone: +39 02 96 70 23 36 Fax: +39 02 96 70 23 69 E-Mail: axson@axson.it

Website: www.sikaadvancedresins.it

AXSON UK LTD

Unit 15 Studlands Park Ind. Estate Newmarket Suffolk, CB8 7AU - UNITED KINGDOM

Phone: +44 1638 660 062 Fax: +44 1638 665 078 E-Mail: sales.uk@axson.com Website: www.sikaadvancedresins.uk

SIKA AUTOMOTIVE SLOVAKIA S.R.O.

Tovarenska 49

953 01 Zlate Moravce - SLOVAKIA Phone: +421 2 5727 29 33

Fax: +421 37 3000 087 E-Mail: SikaAdvancedResins@sk.sika.com

Website: www.sikaadvancedresins.com

SIKA ADVANCED RESINS US

30800 Stephenson Highway Madison Heights, Michigan 48071 - USA

Phone: +1 248 588 2270

Fax: +1 248 616 7452

E-Mail: advanced.resins@us.sika.com Website: www.sikaadvancedresins.us

SIKA AUTOMOTIVE EATON RAPIDS, INC.

1611 Hults Drive

Eaton Rapids, Michigan 48827 - USA

Phone: +1 517 663 81 91 Fax: +1 517 663 05 23

E-Mail: advanced.resins@us.sika.com Website: www.sikaadvancedresins.us

SIKA AUTOMOTIVE MEXICO S.A. DE C.V.

Ignacio Ramirez #20 Despacho 202 Col. Tabacalera C.P. 06030 CDMX - MEXICO

Phone: +52 55 5264 49 22

E-Mail: marketing@axson.com.mx Website: www.sikaadvancedresins.mx

SIKA AUTOMOTIVE SHANGHAI CO. LTD.

N°53 Tai Gu Road Wai Gao Qiao Free Trade Zone, Pudong 200131 Shanghai - CHINA

Phone: +86 21 58 68 30 37 Fax: +86 21 58 68 26 01

E-Mail: marketing.china@axson.com Website: www.sikaaxson.cn

10 F, Shinagawa Intercity Tower B. 2-15-2 Konan, Minato-ku Tokyo 108-6110 - JAPAN Phone: +81 3 6433 2314 Fax: +81 3 6433 2102

E-Mail: advanced-resins@jp.sika.com Website: www.jpn.sika.com

AXSON INDIA PVT. LTD.

Office n°8, Building Symphony C - 3rd Floor

Range Hills Road Bhosale Nagar Pune 411 020 - INDIA Phone: +91 20 25560 710 Fax: +91 20 25560 712 E-Mail: info.india@axson.com

Website: www.sikaadvancedresins.in